

DRETHA IN OIL CHANGE



You get more than you may expect with Harley-Davidson® Authorized Service! Our Regular Service always includes a thorough performance and safety inspection along with so much more. Why risk anything less? Take your Harley-Davidson® motorcycle to the experts who know it best - your Authorized Harley-Davidson® Dealership! Don't get shortchanged – it's more than an oil change!

Check operation of all electrical equinment lighting. and controls.

2 **Inspect front** and rear tyre tread depth and air pressure. Check tightness of all spokes

Inspect fluid level of front brake reservoir. Check torque of cover screws.

(if equipped).

Adjust steering head bearings.

Check torque of switch housing screws, clutch lever handlebar clamp screws, and master cylinder handlebar screws.

Check, adjust and **lubricate throttle** controls

Inspect windshield bushings (if applicable).

> Check torque of upper and lower fork bracket pinch holts

Replace engine oil, filter, and drain

plug O-ring. Torque

drain plug to proper

specification.

Ensure proper oil

level at operating

temperature.

10

Drain and replace

primary chaincase

lubricant and

drain plug O-ring.

Inspect rear brake reservoir for proper level. Check torque of cover screws.

12 Inspect oil, brake, and fuel lines and fittings for leaks, contact, or abrasions.

Drain and replace transmission lubricant and drain plug O-ring.

Inspect front brake pads and discs. Ensure pad thickness is within specification.

15 Inspect rear brake pads and disc. Ensure pad thickness is within specification.

Check torque of brake master cylinder, caliper and ABS HCU banjo bolts.

16 **Check torque** of front and rear axle nut.

18 Inspect and **lubricate** iiffy stand,

Check clutch adjustment.

20 Check, adjust, and lubricate brake and clutch controls.

Inspect and adjust drive belt. Inspect wheel sprocket.

Road test - verify component and system functions.

24

Check for open recalls, product campaigns. trouble codes, and engine system updates.

Check battery, clean connections and torque

terminal screws.

22 Inspect exhaust system for leaks. cracks, and loose or missing fasteners or exhaust shields.



SYN3® oil is the only synthetic lubricant specifically designed for use in your Harley-Davidson® motorcycle.

Regular maintenance will keep your H-D® motorcycle operating at peak performance. Your Harley-Davidson® dealer knows best how to service your motorcycle with factory approved methods and equipment assuring you of thorough and competent workmanship.

Depicted are areas serviced during the recommended 1600 km (1000 mi) service for a 2015 Softail® model. Refer to owner's manual for more details.

